



# AIR-GUARD

## Lubricants Range



### The **complete** solution for compressor lubrication

Rock Oil manufacture and supply a comprehensive range of world-class, high performance compressor oils and product support services. We offer you superior products for rotary screw and reciprocating compressors, ranging from small single units to very large capacity, multi-stage configurations.

**AIR-GUARD**  
2000 VG32

2000 HOURS  
MINERAL

High quality mineral-oil air compressor lubricants. Specially formulated to give up to '2000 hours' fluid life in compressors. Blended using high VI premium grade base oils and selected additives to provide long-term protection and reliability for your compressor.

COMPRESSOR TYPE:  
SCREW



DIN 51 506 VDL • DIN 51 524 PART.2 • AFNOR NF E 48-603 (HM) • SPERRY VICKERS I-286-S • CINCINNATI MILACRON P-68  
Part Number. 11030

**AIR-GUARD**  
2000 VG46

2000 HOURS  
MINERAL

High quality mineral-oil air compressor lubricants. Specially formulated to give up to '2000 hours' fluid life in compressors. Blended using high VI premium grade base oils and selected additives to provide long-term protection and reliability for your compressor.

COMPRESSOR TYPE:  
SCREW/VANE



DIN 51 506 VDL • DIN 51 524 PART.2 • AFNOR NF E 48-603 (HM) • SPERRY VICKERS I-286-S • CINCINNATI MILACRON P-70  
Part Number. 11040

**AIR-GUARD**  
2000 VG68

2000 HOURS  
MINERAL

High quality mineral-oil air compressor lubricants. Specially formulated to give up to '2000 hours' fluid life in compressors. Blended using high VI premium grade base oils and selected additives to provide long-term protection and reliability for your compressor.

COMPRESSOR TYPE:  
VANE/PISTON



DIN 51 506 VDL • DIN 51 524 PART.2 • AFNOR NF E 48-603 (HM) • SPERRY VICKERS I-286-S • CINCINNATI MILACRON P-69  
Part Number. 11050

**AIR-GUARD**  
2000 VG100

2000 HOURS  
MINERAL

High quality mineral-oil air compressor lubricants. Specially formulated to give up to '2000 hours' fluid life in compressors. Blended using high VI premium grade base oils and selected additives to provide long-term protection and reliability for your compressor.

COMPRESSOR TYPE:  
PISTON



DIN 51 506 VDL • DIN 51 524 PART.2 • AFNOR NF E 48-603 (HM) • SPERRY VICKERS I-286-S  
Part Number. 11060

**AIR-GUARD**  
2000 VG150

2000 HOURS  
MINERAL

High quality mineral-oil air compressor lubricants. Specially formulated to give up to '2000 hours' fluid life in compressors. Blended using high VI premium grade base oils and selected additives to provide long-term protection and reliability for your compressor.

COMPRESSOR TYPE:  
HYDROVANE



DIN 51 506 VDL • DIN 51 524 PART.2 • AFNOR NF E 48-603 (HM) • SPERRY VICKERS I-286-S  
Part Number. 11070

**AIR-GUARD**  
5000 VG46

5000 HOURS  
SYNTHETIC

Specially formulated to give up to '5000 hours' fluid life in rotary screw compressors and developed to meet the requirements of Compair and other similar screw compressors to give very long, trouble-free compressor life when a fluid of this viscosity is recommended.

COMPRESSOR TYPE:  
SCREW/VANE



DIN 51 506 VDL • 51 524 PART.2 • VICKERS I-286-S • CINCINNATI MILACRON P-70 • AFNOR NF E 48-603 (HM) • meets OEM specifications for Compair  
Part Number. 00188

## AIR-GUARD 8000 VG32

8000 HOURS  
ULTRA SYNTHETIC PAO

Specially formulated to give up to '8000 hours' fluid life. Full Synthetic EP air compressor oils based on PAO. Recommended for single & multi stage compressors - particularly effective for continuous high temperature arduous operation with exhaust temperatures up to 220°C air temp.

COMPRESSOR TYPE:  
SCREW



DIN 51 506 VDL • DIN 51 524 part.3 • AFNOR NF E 48-603 (HM) • Sperry Vickers I-286-S • Cincinnati Milacron P-68  
Part Number. 11180

## AIR-GUARD 8000 VG46

8000 HOURS  
ULTRA SYNTHETIC PAO

Specially formulated to give up to '8000 hours' fluid life. Full Synthetic EP air compressor oils based on PAO. Recommended for single & multi stage compressors - particularly effective for continuous high temperature arduous operation with exhaust temperatures up to 220°C air temp.

COMPRESSOR TYPE:  
SCREW/VANE



DIN 51 506 VDL • DIN 51 524 part.3 • AFNOR NF E 48-603 (HM) • Sperry Vickers I-286-S • Cincinnati Milacron P-70  
Part Number. 11190

## AIR-GUARD 8000 VG68

8000 HOURS  
ULTRA SYNTHETIC PAO

Specially formulated to give up to '8000 hours' fluid life. Full Synthetic EP air compressor oils based on PAO. Recommended for single & multi stage compressors - particularly effective for continuous high temperature arduous operation with exhaust temperatures up to 220°C air temp.

COMPRESSOR TYPE:  
VANE/PISTON



DIN 51 506 VDL • DIN 51 524 part.3 • AFNOR NF E 48-603 (HM) • Sperry Vickers I-286-S • Cincinnati Milacron P-69  
Part Number. 11200

## AIR-GUARD 8000 VG100

8000 HOURS  
ULTRA SYNTHETIC PAO

Specially formulated to give up to '8000 hours' fluid life. Full Synthetic EP air compressor oils based on PAO. Recommended for single & multi stage compressors - particularly effective for continuous high temperature arduous operation with exhaust temperatures up to 220°C air temp.

COMPRESSOR TYPE:  
PISTON



DIN 51 506 VDL • DIN 51 524 part.3 • AFNOR NF E 48-603 (HM) • Sperry Vickers I-286-S  
Part Number. 11210

## AIR-GUARD 8000 VG150

8000 HOURS  
ULTRA SYNTHETIC PAO

Specially formulated to give up to '8000 hours' fluid life. Full Synthetic EP air compressor oils based on PAO. Recommended for single & multi stage compressors - particularly effective for continuous high temperature arduous operation with exhaust temperatures up to 220°C air temp.

COMPRESSOR TYPE:  
HYDROVANE



DIN 51 506 VDL • DIN 51 524 part.3 • AFNOR NF E 48-603 (HM) • Sperry Vickers I-286-S  
Part Number. 11230

## AIR-GUARD FG VG46

FOOD GRADE  
ULTRA SYNTHETIC PAO

H1 Food Grade Full synthetic compressor oils formulated from the highest quality polyalphaolefin (PAO) base oils with a superior proprietary additive package to achieve long life. AIR-GUARD FG offers a service life of up to '2,000 to 4,000 hours' under a wide range of temperatures under good operating conditions.

COMPRESSOR TYPE:  
SCREW / VANE



Part Number. 14810

## AIR-GUARD FG VG68

FOOD GRADE  
ULTRA SYNTHETIC PAO

H1 Food Grade Full synthetic compressor oils formulated from the highest quality polyalphaolefin (PAO) base oils with a superior proprietary additive package to achieve long life. AIR-GUARD FG offers a service life of up to '2,000 to 4,000 hours' under a wide range of temperatures under good operating conditions.

COMPRESSOR TYPE:  
VANE / PISTON



Part Number. 14820

## AIR-GUARD FG VG100

FOOD GRADE  
ULTRA SYNTHETIC PAO

H1 Food Grade Full synthetic compressor oils formulated from the highest quality polyalphaolefin (PAO) base oils with a superior proprietary additive package to achieve long life. AIR-GUARD FG offers a service life of up to '2,000 to 4,000 hours' under a wide range of temperatures under good operating conditions.

COMPRESSOR TYPE:  
PISTON



Part Number. 14870

## AIR-GUARD ROCKFROST

Specifically designed for the lubrication of percussion type air tools operating in very cold conditions. Absorbs the water in the air, depressing the freezing point of the solution formed, thus eliminating freezing. AIR-GUARD ROCKFROST is ideal for water well drilling, as it washes out the hole with the first rush of water.



Part Number. 04110

## AIR-GUARD AIRLINE OIL VG22

A high quality lubricant blended from solvent refined, naphthenic base oils and selected additives, AIR-GUARD AIRLINE OIL is designed specifically as an airline lubricant for use on pneumatic tools. Aids the drawing out of water from the air system. Ensures fresh, dry air for the efficient use of the air tools, and equipment.



Part Number. 04081

## AIR-GUARD AIRLINE OIL FG VG22

AIR-GUARD AIRLINE OIL FG is specially formulated, synthetic hydrocarbon, food grade, non-toxic lubricant developed for pneumatic airline systems used on food, drink and pharmaceutical processing and packaging equipment. Also suitable for other compressed air systems where a clean, non-staining product is desired.



Part Number. 14830



✓ MALONE HOUSE, 90 PRIESTLEY STREET, WARRINGTON, CHESHIRE, WA5 1ST, UNITED KINGDOM

☎ +44 (0) 1925 636191

f ROCKOIL.LUBRICANTS

@ SALES@ROCKOIL.CO.UK

🐦 ROCKOILNEWS

🌐 ROCKOIL.CO.UK

📺 ROCKOILNEWS

