

The pursuit of excellence has resulted in the highly prestigious NMMA certification for our cutting edge MP3 Ultra, Bio Marine 3, MP3 Sport and MP+ lubricants. Using the correct lubricant is essential in ensuring the long term reliability and protection of your engine. Every Rock Oil marine product is engineered to perform a specific task, assuring you of the highest performance for your own individual requirements.



MP3 ULTRA OUTBOARD



MP3 Ultra is a high performance, NMMA TC-W3®, synthetic blend 2-stroke outboard oil, developed for use with the latest Direct Fuel Injection (DFI) engines and their special lubrication requirements.

NMMA TC-W3® (No. RL 92402B) Synthetic Blend 2-stroke Outboard Oil



BIO MARINE 3 OUTBOARD



BIO Marine 3 is a bio-degradable ester based fluid which offers outstanding performance. Using the most advanced ashless additives, BIO Marine 3 achieves maximum power whilst maintaining engine life of 2-stroke outboard engines.

NMMA TC-W3® Fully Synthetic 2-stroke Outboard Oil



MP+ SPORT 10W-40 OUTBOARD



Blended from the highest quality base oil with state of-the art synthetic additives, MP+ Sport semi-synthetic engine oil is a specially designed NMMA FC-W accredited lubricant for use in all modern 4-stroke outboard engines.

NMMA FC-W CC (No. FC13799W) 4-stroke Outboard Oil



MP4 SPORT INBOARD

MP4 Sport engine oil is a premium grade 4-stroke engine oil designed for the latest generation of high performance inboard engines.

API CI-4+ CI-4/SI • ACEA A3/B4 E7 (incl E3 & E5 obsolete specs) • CATERPILLAR ECF-2, ECF-1a • CUMMINS CES 20078, 20077, 20076, 20072, 20071 • DDC 93K215 • DEUTZ DQC-II-05, DQC-II-10 • JASO DH-1 • MACK EO-M PLUS, EO-M • MAN M3275 & M271 • MERCEDES-BENZ 228.3 228.1, 229.1 • MTU TYPE 2 & 1 • RVI RLD-2, RLD VOLVO VDS-3 VDS-2 & VDS



MP LITE-D

MULTIGRADE DIESEL OIL

MP Lite-D is a high quality multigrade oil suitable for use in small capacity non-turbo diesel engines, and is equally applicable to engines where the manufacturer recommends a 10W-30, 10W-40 or a 15W-40 API SF/CC engine oil.



API SF/CC Diesel Engine Oil

MPR INJECTOR

NON TC-W3® 2-STROKE ENGINE OIL

MPR Injector is a fully synthetic high performance 2-stroke marine lubricant, most suited for use in an injector system but can be used as a premix oil. MPR Injector is a smokeless, ultra clean burning lubricant with exceptional performance.

Non TC-W3® JASO FD & FC • ISO L-EGD • API TC ROTAX 253 • HUSQVARNA 346 & 372



MP Gear Oil is developed from

MP MARINE GEAR OIL

the finest base stocks available combined with state-of-the-art extreme pressure (EP) additives for use in hypoid axles and gear boxes.



MARINE PSF OUTBOARD

Marine PSF is a multi-functional power steering and hydraulic fluid, which satisfies the requirements of most major marine equipment manufacturers. It is suitable for use in marine power trim units and hydraulic steering applications.



GM Dexron II

MARINE HSF

Marine HSF is a premium hydraulic steering fluid which satisfies the requirements of major marine equipment manufacturers. Marine HSF comprises of a high quality blend of viscosity stabilizers, anti-wear agents and corrosion inhibitors.

Suitable for: Seastar™, Baystar™, & Hynautic™ steering systems



MG UNIVERSAL MARINE GREASE

API GL-5

MARINE INBOARD & OUTBOARD

MG Universal Marine Grease is a multi-purpose lithium based grease containing zinc oxide additive to repel moisture. suitable for use in marine outboard and inboard engines.

Versatile multi purpose grease Excellent water resistance Excellent corrosion protection Good sealing properties



MG STERN TUBE GREASE

MARINE INBOARD & OUTBOARD

MG Stern Tube Grease is a premium quality, water resistant grease for use in industrial & marine applications where the presence of water and humid atmospheres can effect lubricating performance

Premium quality grease Extremely high degree of water resistance Excellent corrosion protection Good sealing properties



KOOL-GUARD MARINE MPG



Non-toxic, ready to use antifreeze that will provide burst protection to -46°C and freeze protection within a range of -10°C. Use in boats, motor homes, mobile homes, pools. Protects water systems & engines from freeze ups during storage. Safe for copper, brass and all types of plastic. Contains corrosion inhibitors to protect all metal engine components and seals

ASTM D3306 TYPE II • BS 6580 (2010) • AFNOR NF R15-601 (except reserve alkalinity)





Kool-Guard MEG -38 is an ethylene alvcol-based, ready to use engine coolant, suitable for use in many vehicles. Kool-Guard MEG -38 provides long lasting corrosion protection, and provides freeze protection down to -38°C.



KOOL-GUARD

XL -38



Kool-Guard XL -38 is an ethylene alvcol-based, ready to use engine coolant, which employs Organic Acid Inhibitor Technology. Suitable for use in all vehicles including those using Aluminium Alloy materials. Kool-Guard XL -38 has excellent hard water stability and very low inhibitor depletion rates. Provides freeze protection down to -38°C.



ASTM D3306, D4985 • BS 6580 (2010) • SAE J1034 • FFV Heft R443 • CUNA NC 956-16 • UNE 26361-88 • JIS K2234 • NATO S759 • AFNOR NF R15-601 (except for reserve alkalinity)

ROCKEZE

Rockeze is a light hydrocarbon solvent and has been treated with the most advanced rust and corrosion inhibitors, dewatering agent and friction modifiers. This allows Rockeze to provide superior penetrating and light anti-rust capabilities and for it to be used in limitless applications.



MAR

SILICONE PROTECTOR SPRAY

BS 6580 (2010) • ASTM D3306 • SAE J1034 • AFNOR NR R 15-601- 1991

Protector silicone spray is a fast shining blend of cleaning solvents and silicones. It brings vinvl. paint work and plastic back to a sparkling appearance, especially effective on black metal work. Removes oil and stains. It can be used on glass and perspex and as a non-staining lubricant on linkages and locks.



SUPER **MARINE INHIBITOR**

400ml AEROSOL

Super Marine Inhibitor spray consists of a light mineral oil blended with sophisticated corrosion inhibitors and oxidation stabilisers. May be used on external surfaces where it yeilds a water repellent lubricated surface which prevents rust formation.





🔆 KOOL-GUARD MEG AND KOOL-GUARD XL ALSO AVAILABLE IN CONCENTRATE FOR DILUTION



- MALONE HOUSE, 90 PRIESTLEY STREET, WARRINGTON, CHESHIRE, WAS IST, UNITED KINGDOM
- +44 (0) 1925 636191
- SALES@ROCKOIL.CO.UK
- ROCKOIL.CO.UK







